

Inseal EX208 Butyl Tape Technical Data Sheet

Welcome to Inseal

At Inseal, we take pride in our commitment to quality and innovation. Our **EX208 Butyl Tape** is designed to meet your adhesive needs with exceptional performance and reliability.

Product Overview

EX20 Butyl Tape is a highly adhesive, tacky mastic that bonds effortlessly to a variety of surfaces. This product ensures durable adhesion both in packaging and as a weather-tight seal. You can trust that it will not adversely affect lacquer, painted surfaces, or Plexiglas, making it a versatile choice for many applications.

Applications

Our EX208 Butyl Tape is ideal for:

- **Sealing roof seams** on metal buildings, manufactured housing, and RVs.
- **Constructing wall panels** and channel glazing.
- **Used on seams for truck and trailer bodies.**
- **Sealing joints for ducts and chambers** for air conditioning, as well as shower doors, windows, and doors in manufactured housing and RVs.

Why Choose Inseal EX208 Butyl Tape?

- **Excellent Adhesion:** Our tape sticks well to most surfaces, ensuring a strong, lasting bond.
- **Weather Resistance:** It offers superior protection against water and air intrusion, standing up to the elements.
- **User-Friendly:** Designed for ease of application, it can be trimmed to fit your specific needs effortlessly.

Partner with us at Inseal

We believe that quality products empower you to achieve remarkable results. By choosing **EX208 Butyl Tape**, you're selecting a product that stands out in performance and reliability, crafted with care to support your projects.

For any questions or further assistance, our team is here to help.

Product Specifications

TYPICAL PHYSICAL PROPERTIES and GENERAL INFORMATION

| Property | Value |
|----------------------------------|-------------------------------|
| Raw Material Base | Synthetic Resin |
| Needle Penetration @ 78° F, 150g | 10.5 - 11.5 mm |
| Color | Gray Black |
| Specific Gravity | 1.66 - 1.95 |
| Elongation @ 77° F | >300 % |
| Weight Per Gallon | 15 - 16 lb. |
| Solids By Weight | 99% |
| Flash Point | 325°F (162°C) |
| Temperature Range | -40°F (-40°C) to 180°F (82°C) |
| Shelf Life | One Year |

This product has 0 VOC and is 100% solid

Selection Guide

| Dimensions INCH Thickness x Width x Length | Color | Rolls Per Carton | Part Number |
|--|------------|---------------------|----------------|
| 1/8" x 1/2" x 50' | Black/Gray | 18 | EX208-13-1812 |
| 1/8" x 3/4" x 50' | Gray | 8 | EX208-17-1834 |
| 1/8" x 1" x 50' | Gray | 10 | EX208-17-1810 |
| 1/8" x 1 1/2" x 50' | Black | 6 | EX208-13-1815 |
| 1/8" x 2" x 50' | Gray | 4 | EX208-17-1820 |
| 3/16 x 1/4 x 40' | Gray | 26 | EX208-17-3161 |

Customizable Sizes and selective Colors Are Available Upon Request

**We Have Available Options for Custom Cut Lengths
Per Customer Request**

All sizes sold 32 cartons per pallet. All pallets are shrink wrapped to increase resiliency.
Contact our Customer Service Department